




Recommended Wheel Position



Features



Urban Application



Enhanced Mileage



Optimized Handling



Multiple Retreads

CT518+ : All Wheel Position

Size	Load Index/ Speed Index	PR	TT/TL	Maximum Load (kg/lbs)	Maximum Pressure (kpa/psi)	Meas. Rim Width (inch)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
11R22.5	144/142L	14	TL	(S) 2800/6175 (D) 2650/5840	720/105	8.25	1052	282	12.7
11R22.5	148/145L	16	TL	(S) 3150/6940 (D) 2900/6395	850/123	8.25	1052	282	12.7
295/75R22.5	144/141L	14	TL	(S) 2800/6175 (D) 2575/5675	760/106	9.00	1014	296	12.7
11R24.5	144/142L	14	TL	(S) 2800/6175 (D) 2650/5840	720/106	8.25	1102	282	12.7
11R24.5	146/143L	14	TL	(S) 3000/6610 (D) 2750/6005	830/120	8.25	1102	282	12.7
285/75R24.5	144/141L	14	TL	(S) 2800/6175 (D) 2575/5675	760/106	8.25	1054	283	12.7

- 5 rib tread design with wide shoulder for excellent handling stability
- 4 wide straight grooves for efficient water evacuation and breaking performance in both wet and dry conditions
- Advanced construction and compound design for high speed and long distance performance
- Strengthened casing for more retreads