




## Recommended Wheel Position



## Features



Regional Application



Enhanced Mileage



Optimized Handling



Multiple Retreads

## CT588+ : All Wheel Position

Size	Load Index/ Speed Index	PR	TT/TL	Maximum Load (kg/lbs)	Maximum Pressure (kpa/psi)	Meas. Rim Width (inch)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
215/75R17.5	126/124L	14	TL	(S) 1700/3750 (D) 1600/3255	690/100	6.00	776	225	12.7
215/75R17.5	135/133J	16	TL	(S) 2180/4805 (D) 2060/4540	850/122	6.00	776	225	12.7
235/75R17.5	143/141L	16	TL	(S) 2725/6008 (D) 2575/5677	790/115	6.75	797	233	14.0
225/70R19.5	121/119L	10	TL	(S) 1450/3195 (D) 1360/3000	550/80	6.75	811	226	12.7
225/70R19.5	128/126M	14	TL	(S) 1800/3970 (D) 1700/3750	760/110	6.75	811	226	12.7
245/70R19.5	135/133L	16	TL	(S) 2180/4805 (D) 2060/4540	830/120	7.50	839	248	14.0
265/70R19.5	140/138L	16	TL	(S) 2500/5510 (D) 2360/5205	830/120	7.50	873	262	14.0
10.00R20	146/143L	16	TT	(S) 3000/6610 (D) 2725/6005	830/120	7.50	1051	274	15.9
11.00R20	150/147K	16	TT	(S) 3350/7390 (D) 3075/6780	830/120	8.00	1095	298	16.0
12R22.5	150/147K	16	TL	(S) 3350/7390 (D) 3075/6780	830/120	9.00	1085	300	16.0
295/80R22.5	150/147M	16	TL	(S) 3350/7390 (D) 3075/6780	830/120	9.00	1055	290	16.7
295/80R22.5	152/149M	18	TL	(S) 3550/7830 (D) 3250/7160	900/130	9.00	1055	290	16.7
315/80R22.5	154/151M	18	TL	(S) 3750/8270 (D) 3450/7610	830/120	9.00	1083	318	17.5
315/80R22.5	158/150L	20	TL	(S) 3750/8270 (D) 4250/9370	900/130	9.00	1083	318	17.5

- 5 rib tread design with wide shoulder for excellent handling
- 4 wide straight grooves for efficient water evacuation and breaking performance in wet and dry conditions
- Advanced construction and compound design for high-speed and long distance performance
- Strengthened casing for more retreads