




Recommended Wheel Position



Features



Off Road Application



Enhanced Mileage



Chip Resistant



Extra Traction



Multiple Retreads

CT601+ : On/Off Road All Wheel Position

Size	Load Index/ Speed Index	PR	TT/TL	Maximum Load (kg/lbs)	Maximum Pressure (kpa/psi)	Meas. Rim Width (inch)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
7.50R16LT	122/121L	14	TL	(S) 1510/3330 (D) 1450/3195	690/100	6.00	805	203	12.7
9.00R20	141/139K	14	TT	(S) 2575/5675 (D) 2430/5355	790/115	7.00	1028	258	15.0
10.00R20	146/143K	16	TT	(S) 3000/6610 (D) 2725/6005	830/120	7.50	1059	272	15.9
11.00R20	150/147K	16	TT	(S) 3350/7390 (D) 3075/6780	830/120	8.00	1084	291	16.7
11R22.5	144/142L	14	TL	(S) 2800/6175 (D) 2650/5840	720/105	8.25	1060	285	16.6
11R22.5	146/143L	16	TL	(S) 3000/6610 (D) 2725/6005	830/120	8.25	1060	285	16.6
385/65R22.5	160K	20	TL	(S) 4500/9920	900/130	11.75	1072	386	16.0
315/80R22.5	157/154L	20	TL	(S) 4120/9090 (D) 3750/8270	900/130	9.00	1076	312	17.5
11R24.5	149/146L	16	TT	(S) 3250/8270 (D) 3000/7610	830/120	8.00	1186	293	17.5
12R24.5	152/149K	16	TL	(S) 3550/7830 (D) 3250/7160	830/120	9.00	1135	300	17.5

- Combination of rib and lug pattern for high traction and superior resistance to irregular wear
- 3 zigzag grooves for excellent grip performance on wet, dry or snowy roads
- Advanced cut and chip compound provides anti-abrasion and resistance to cutting and tearing
- Strengthened casing for more retreads