




Recommended Wheel Position



Features



Regional Application



Enhanced Mileage



Optimized Handling



Multiple Retreads

CT701+ : Drive Wheel Position

Size	Load Index/ Speed Index	PR	TT/TL	Maximum Load (kg/lbs)	Maximum Pressure (kpa/psi)	Meas. Rim Width (inch)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
11R22.5	144/142L	14	TL	(S) 2800/6175 (D) 2650/5840	720/105	8.25	1054	279	23.5
11R22.5	146/143L	16	TL	(S) 3000/6610 (D) 2725/6005	830/120	8.25	1054	279	23.5
11R22.5	148/145L	16	TL	(S) 3150/6940 (D) 2900/6395	850/123	8.25	1054	279	23.5
295/80R22.5	150/147L	16	TL	(S) 3350/7390 (D) 3075/6780	830/120	9.00	1052	298	23.5
295/80R22.5	152/149L	18	TL	(S) 3550/7830 (D) 3250/7160	900/130	9.00	1052	298	23.5
315/80R22.5	154/151L	18	TL	(S) 3750/8270 (D) 3450/7610	830/120	9.00	1083	314	23.8
315/80R22.5	158/150L	20	TL	(S) 4250/9370 (D) 3350/7390	900/130	9.00	1082	314	23.8
11R24.5	146/143L	14	TL	(S) 3000/6610 (D) 2725/6005	720/105	8.25	1097	275	23.8
11R24.5	149/146L	16	TL	(S) 3250/7160 (D) 3000/6610	830/120	8.25	1097	275	23.8

- Block pattern and open shoulder design for excellent traction and superior resistance to irregular wear
- Block and groove design for excellent grip performance on wet, dry or snowy roads
- Advanced compound and construction for loading performance and increased durability
- Strengthened casing for more retreads