



- 3 centric rib design offers excellent performance on wet and dry roads
- 4 main grooves that enable extra drainage
- Wide tread design for extra contact space

Features



Enhanced Mileage



Optimized Handling

EL JEFE H/T

Size		Load Index	Speed Rating	UTQG	Rim Width Measure (inches)	Max Air psi	Max Load Capacity (lbs) Single	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
215/70R16		100	T	500AA	6.5	43.5	800	708	221	8.5
235/70R16		106	T	500AA	7.0	43.5	950	736	240	8.5
245/70R16 XL		111	T	500AA	7.0	50	1090	750	248	8.5
255/70R16		111	T	500AA	7.5	43.5	1090	764	260	8.5
265/70R16		112	T	500AA	8.0	43.5	1120	778	272	8.8
225/65R17		102	H	500AA	6.5	43.5	850	724	228	8.5
235/65R17		104	H	500AA	7.0	43.5	900	738	240	8.5
245/65R17 XL		111	T	500AA	7.0	50	1090	750	248	8.5
265/65R17		112	H	500AA	8.0	43.5	1120	776	272	8.8
265/70R17		115	T	500AA	8.0	43.5	1215	804	272	8.8
235/60R18		103	H	500AA	7.0	43.5	875	739	240	8.5
235/65R18		106	H	500AA	7.0	43.5	950	763	240	8.5
265/60R18		110	H	500AA	8.0	43.5	1180	801	272	8.8
275/65R18		116	H	500AA	8.0	43.5	1250	815	279	8.8



Includes industry-leading Road-Hazard Warranty. See page 14 for more details.