



- Quiet ride technology
- 4 main grooves that enable extra drainage
- Advanced rubber compound and extra plies resist cuts and punctures
- All-season design with closed shoulders for added safety

Features



Enhanced Mileage



Optimized Handling

EL JEFE H/T²

Size	PLY Rating	Load Index	Speed Rating	UTQG	Rim Width Measure (inches)	Max Air psi	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	NSD 32	
LT235/75R15	RH	8	116/113	Q	-	6.50x15	65	732	239	10.20	12.85
LT215/85R16	RH	10	115/112	Q	-	6.00x16	80	769	219	10.20	12.85
LT225/75R16	RH	10	115/112	Q	-	6.00x16	80	744	226	10.20	12.85
LT235/85R16	RH	10	120/116	Q	-	6.50x16	80	802	235	10.20	12.85
LT245/75R16	RH	10	120/116	Q	-	7.00x16	80	774	250	10.20	12.85
LT265/75R16	RH	10	123/120	Q	-	7.50x16	80	804	272	10.20	12.85
LT285/75R16	RH	10	126/123	Q	-	8.00x16	65	832	292	10.20	12.85
LT235/80R17	RH	10	120/117	Q	-	6.50x17	80	807	239	10.20	12.85
LT265/70R17	RH	10	121/118	Q	-	8.00x17	80	803	270	10.20	12.85
LT285/70R17	RH	10	121/118	Q	-	8.50x17	80	831	291	10.20	12.85



Includes industry-leading Road-Hazard Warranty. See page 20 for more details.